



Industrial Printers


EZ2250i / EZ2350i

Enhanced mid-range industrial barcode printer for most applications

All metal mechanism design featuring die-cast center plane and base make EZ2250i series perfect for high volume applications



Color TFT LCD and operation panel for easy and intuitive operation



USB Host for extension memory and standalone operation



All metal, industrial enclosure and print mechanism



Automatic self adjustment for coated inside/outside ribbons

GoDEX

COLUMBIA
FRANCE
MARQUAGE

EZ2250i/EZ2350i Printer Specification

2024-11-18

Model	EZ2250iEZ2350i	
Print Method	Thermal Transfer / Direct Thermal	
Resolution	203 dpi (8 dot/mm)	300 dpi (12 dots/mm)
Print Speed	7 IPS (177 mm/s)	5 IPS (127 mm/s)
Print Width	4.09" (104 mm)	
Print Length	Min. 0.16" (4 mm)**; Max. 100" (2540 mm)	Min. 0.16" (4 mm)**; Max. 45" (1143 mm)
Processor	32 Bit RISC CPU	
Memory	8 MB Flash (4 MB for user storage) ; 16 MB SDRAM	
Sensor Type	Adjustable reflective sensor and transmissive sensor, left aligned	
Media	Types : Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming	
	Width : Min. 0.8" (20 mm) – Max. 4.65" (118 mm)	
	Thickness : 0.0024" (0.06 mm) – Max. 0.01" (0.25 mm)	
	Label Roll Diameter : Max. 8" (203.2 mm) with 3" (76.2 mm) core Max. 6" (152.4 mm) with 1.5" (38.1 mm) core Core Diameter : 1.5" (38.1 mm) - 3" (76.2 mm)	
Ribbon	Types : Wax, wax / resin, resin Length : 1476' (450 m) Width : Min. 1.18" (30 mm) – Max. 4.33" (110 mm) Ribbon Roll Diameter : 2.99" (76 mm) Core Diameter : 1" (25.4 mm)	
Printer Language	EZPL, GEPL, GZPL, GDPL auto switch	
Software	Label design tool: GoLabel II (for EZPL only) (Windows) Management tools: GoTools (Windows / Android) \ GoUtility (Windows)	
Driver	Windows 7, Windows 8 & 8.1, Windows 10, Window11, Windows Server 2008 R2, 2012, 2012 R2, 2016, 2019, 2022, MAC, Linux	
SDK	Win CE, .NET, Windows 7, Windows 8 & 8.1, Windows 10, Windows 11, Android, Mac, iOS	
Resident Fonts	Bitmap fonts: 6, 8, 10, 12, 14, 18, 24, 30, 16X26 and OCR A & B 0°, 90°, 180°, 270° rotatable, single characters 0°, 90°, 180°, 270° rotatable	
	8 times expandable in horizontal and vertical directions TTF Fonts: (Bold / Italic / Underline) 0°, 90°, 180°, 270° rotatable	
	Bitmap fonts: 0°, 90°, 180°, 270° rotatable, single characters 0°, 90°, 180°, 270° rotatable	
Download Fonts	Asian fonts: 16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese(GB2312), Japanese(S-JIS), Korean (KS-X1001) 0°, 90°, 180°, 270° rotatable and 8 times expandable in horizontal and vertical directions	
	TTF fonts: (Bold / Italic / Underline). 0°,90°, 180°, 270° rotatable	
Barcodes	1-D Bar codes: China Postal Code, Codabar, Code 11, Code 32,Code 39, Code 93, Code 128 (subset A, B, C), EAN-8/EAN-13 (with 2 & 5 digits extension), EAN 128, FIM, German Post Code, GS1 DataBar, HIBC, Industrial 2 of 5 , Interleaved 2-of-5 (12 of 5), Interleaved 2-of-5 with Shipping Bearer Bars, ISBT-128, ITF 14, Japanese Postnet, Logmars, MSI, Postnet, Plessey, Planet 11 & 13 digit, RPS 128, Standard 2 of 5, Telepen, Matrix 2 of 5, UPC-A/UPC-E (with 2 or 5 digit extension), UCC/EAN-128 K-Mart, Random Weight and Pharmacode	
	2-D Bar codes: Aztec code, Code 49,Codablock F , Datamatrix code, MaxiCode, Micro PDF417, Micro QR code, PDF417,QR code, TLC 39, GS1 Composite, DotCode, Marco PDF 417	
Code Pages	Codepage 437, 737,850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869	
	Windows 1250, 1251, 1252, 1253, 1254, 1255, 1257 Unicode UTF8, UTF16BE, UTF16LE	
Graphics	Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software	
Interfaces	USB 2.0 (Type B)	
	Serial port (RS232)	
	Ethernet 10/100 Mbps USB Host (Type A)	
Real Time Clock	Standard	